



Stock program titanium and titanium alloys for electroplating

Your contact partner

Dorothea Röhrig

Product Manager Surface Treatment

☎ +49 211 230 999-20

✉ d.roehrig@sd-metals.com

First class quality high performance products – CP – titanium, round bars, coils, sheets, plates and tubes in following standard dimensions and sizes

CP titanium jig-section, Hexagon bars, Titanium wire, Titanium sheets

Round bars

Grade 2 ASTM B348 + F67

- | | | | |
|-------------|-------------|--------------|--------------|
| ▪ 4.0 mm Ø | ▪ 20.0 mm Ø | ▪ 65.0 mm Ø | ▪ 130.0 mm Ø |
| ▪ 5.0 mm Ø | ▪ 25.0 mm Ø | ▪ 70.0 mm Ø | ▪ 140.0 mm Ø |
| ▪ 6.0 mm Ø | ▪ 30.0 mm Ø | ▪ 75.0 mm Ø | ▪ 150.0 mm Ø |
| ▪ 8.0 mm Ø | ▪ 35.0 mm Ø | ▪ 80.0 mm Ø | ▪ 170.0 mm Ø |
| ▪ 10.0 mm Ø | ▪ 40.0 mm Ø | ▪ 90.0 mm Ø | ▪ 180.0 mm Ø |
| ▪ 12.0 mm Ø | ▪ 45.0 mm Ø | ▪ 95.0 mm Ø | ▪ 190.0 mm Ø |
| ▪ 15.0 mm Ø | ▪ 50.0 mm Ø | ▪ 100.0 mm Ø | ▪ 200.0 mm Ø |
| ▪ 16.0 mm Ø | ▪ 55.0 mm Ø | ▪ 110.0 mm Ø | ▪ 250.0 mm Ø |
| ▪ 19.0 mm Ø | ▪ 60.0 mm Ø | ▪ 120.0 mm Ø | |

CP titanium jig-section

ASTM B 348 in random lengths of min. 2.7 to c. 4 m

- | | | | |
|--------------------|--------------------|--------------------|--------------------|
| ▪ 6.35 x 6.35 mm | ▪ 15.00 x 15.00 mm | ▪ 12.70 x 6.35 mm | ▪ 25.40 x 6.35 mm |
| ▪ 9.50 x 9.50 mm | ▪ 19.05 x 19.05 mm | ▪ 19.05 x 6.35 mm | ▪ 25.40 x 12.70 mm |
| ▪ 12.70 x 12.70 mm | ▪ 25.40 x 25.40 mm | ▪ 19.05 x 12.70 mm | |

Hexagon bars, Grade 2

ASTM B 348 cold drawn, annealed

- AF 10 mm
 - AF 13 mm
 - AF 17 mm
 - AF 19 mm
-

Sheets Grade 4

ASTM B 265

- 0.50 mm
 - 0.70 mm
 - 0.80 mm
 - 1.00 mm
 - 1.27 mm
 - 1.57 mm
 - 2.00 mm
 - 3.00 mm
-

Titanium wire, Grade 3

spring tempered ASTM B 863

- 1.5 mm Ø
 - 2.0 mm Ø
 - 2.5 mm Ø
 - 3.0 mm Ø
 - 4.0 mm Ø
 - 5.0 mm Ø
-

Titanium wire, Grade 4

spring tempered random length c. 2-3 m ASTM B 863 | B 348

- 2.0 mm Ø
 - 2.5 mm Ø
 - 3.0 mm Ø
 - 4.0 mm Ø
 - 5.0 mm Ø
 - 6.0 mm Ø
 - 8.0 mm Ø
-

Sheets | Plates Grade 2

ASTM B 265 | ASME SB 265

- 5.0 mm
 - 6.0 mm
 - 8.0 mm
 - 10.0 mm
 - 12.0 mm
 - 15.0 mm
 - 20.0 mm
 - 25.0 mm
 - 30.0 mm
 - 35.0 mm
 - 40.0 mm
 - 50.0 mm
-